

Specifications

Hybrid+ PK15 UE

Type	Multi-purpose 15" full-range speaker
RMS / Peak Power (AES)	500W / 2000W
Nominal Impedance	8 Ohm
Average Sensitivity	98dB / 1W / 1m
Maximum SPL (Calculated)	125dB RMS / 131dB Peak
Frequency Response	47Hz – 18kHz
Nominal Directivity	80° (H) x 50° (V), rotatable horn
LF Driver	CELTO Acoustique 15MB458-8
Woofers Chassis	Die-cast aluminum
Woofers Voice Coil Diameter	3" / 75mm
HF Driver	CELTO Acoustique PCD440B
HF RMS Power (AES)	50W (above 1600Hz)
HF Exit Size	1" / 25mm
HF Voice Coil Diameter	1.7" / 44mm
HF Diaphragm Material	Keytone polymer
Crossover (Integrated)	LF: 2000Hz, 12dB/oct HF: 2000Hz, 18dB/oct
Cabinet Material	Exterior grade birch plywood
Cabinet Finish	UltraTex (USA) textured black coating – 3 coat
Grille	Two-tone, 1.2mm curved steel, black powder coated
Floor Monitor Use	No
Flying Hardware	7 x M8 points
Mounting Hardware	Dual angle pole mount (0° & 10°)
Connectors	2 x NEUTRIK NL4MP
Cabinet Dimensions (HxWxD)	660 x 410 x 415mm
Cabinet Weight	20Kg