



Specifications

HYBRID ML860PDUU

HYBRID ML1260PDUU

Mixer Type	Powered, Small Format Analogue Live Mixer	Powered, Medium Format Analogue Live Mixer
Mono Input Channels	4 × XLR (Mic) / 1/4" Jack (Line)	8 × XLR (Mic) / 1/4" Jack (Line)
Mono Channel Faders	45mm Level Faders	45mm Level Faders
Channel EQ	3-Band Rotary (Low, Mid, High)	3-Band Rotary (Low, Mid, High)
Mono Channel Controls	Low Cut Switch, Pan, Effects Send, Peak LED	Low Cut Switch, Pan, Effects Send, Peak LED
Stereo Channel Controls	45mm Level Fader, -10dB Switch, Balance, Peak LED	45mm Level Fader, -10dB Switch, Balance, Peak LED
MP3 Media Player	USB Port (Play & Record)	USB Port (Play & Record)
Audio Interface	USB B	USB B
Built-in Effects	16 DSP, 45mm Effects Level Fader, FX Send	16 DSP, 45mm Effects Level Fader, FX Send
Master Channel Controls	Dual 45mm L/R Main Faders, 5-Band Graphic EQ, Headphone Volume, MP3 Level, 48V Phantom, Dual 8- LED Meter	Dual 45mm L/R Main Faders, 5-Band Graphic EQ, Headphone Volume, MP3 Level, 48V Phantom, Dual 8- LED Meter
Powered Output	2 × 300W RMS @ 4Ω (Both Channels Driven)	2 × 300W RMS @ 4Ω (Both Channels Driven)
Speaker Output Connectors	2 × Speakon & 2 × 1/4" Jack	2 × Speakon & 2 × 1/4" Jack
Max Load per Channel	4Ω	4Ω